

# GYSMATIC 2.0 CL XXL TRUE COLOR



REF. 069138

The GYSMATIC 2.0 CL XXL, with its light colour 2, offers perfect visibility. Its XXL screen and panoramic field of vision guarantee a wide, unobstructed view. With 5 highly sensitive sensors, it reacts instantly to the welding arc. The multipremium headband ensures a secure, comfortable fit, reducing fatigue during prolonged use. What's more, its automatic adjustment adjusts the tint according to the intensity of the arc.

## FEATURES

- **Clear shade 2**, exceptional visibility before welding.
- **Panoramic field of vision:** 1 XXL screen + 2 fixed-tint side screens for 180° vision.
- **Intelligent mask** with automatic parameter settings according to working conditions (light, mode, etc).
- **5 extremely sensitive sensors** for maximum efficiency.
- **Multi premium headband** fully adjustable. Optimised balance point for exceptional levels of comfort.
- Ergonomic **control panel with digital screen**.
- **Filter with TrueColor technology:** more realistic and detailed colour reproduction than conventional filters.



Classic  
★

TrueColor  
★★★★

## TECHNICAL TABLE

|                      |                                                                   |         |
|----------------------|-------------------------------------------------------------------|---------|
| UV/IR protection     | DIN 15                                                            |         |
| Classification       | 1/1/1/2                                                           |         |
| Light tint           | 2                                                                 |         |
| Dark tint            | Main: 4 - 8 / 8 - 12                                              | Side: 5 |
| Reaction time        | 0.08 ms                                                           |         |
| Clear reversion time | 0.06 to 1.0 sec                                                   |         |
| Field of vision      | Main: 100 x 93 mm<br>Side screens: 125 x 66 mm (x2)               |         |
| Energy               | solar + 2 batteries (CR2032)                                      |         |
| Weight               | 550 g                                                             |         |
| Settings             | Manual / Automatic<br>Sensitivity, delay, tint, welding, grinding |         |
| Light sensor         | 5                                                                 |         |
| Application fields   | MMA 5 ▶ 400 / TIG 2 ▶ 300 / MIG-MAG 5 ▶ 400                       |         |
| Standards            | CE / EN 175B / EN 166 / EN 379                                    |         |



Clear shade 2



Clear shade 3



- 1 SHADE: Tint setting (4>8 / 8>12)
- 2 SENS: Sensitivity setting (0>7)
- 3 DELAY: Clearance time setting

## ACCESSORIES

Mask cover  
043299




Mask backpack  
066656



Sweatband  
x2  
043466



Spare screens



Magnifying  
glass (x1)  
**zoom x2**  
042780  
**zoom x3**  
064140