



Max. load capacity flat, from 10mm material thickness:  
 horizontal = 135 kg  
 vertical = 45 kg  
 Max. load capacity round Ø 50-205mm, from 10mm material thickness  
 horizontal = 135 kg  
 vertical = 45 kg  
 At workpiece temperature 100°C - Max. contact time 100%  
 At workpiece temperature 170°C - Max. contact time = 5 min. / 50%  
 Contact time = cooling time at 30°C ambient temperature

Schutzvermerk nach DIN ISO 16016 beachten! Nachdruck nur mit unserer Genehmigung!					tolerance	material:	weight: 18.00 kg		
All rights reserved according to DIN ISO 16016! Reprint with our permission only!					ISO 7168 M	drawing no.:	0012020		
				date	name	description: <b>FX-HVS-R225</b>			
				drawn 07.12.2020	FEU	Horizontal-vertical slewing magnet			
07	Green Dot	01.02.2024	TW	edit 15.02.2024				part no.: 11030221	
06	Hebel	08.12.2023	TW	appr. 15.02.2024	TW				
05	Ganter Griff	25.10.2023	FEU	 www.flraig-te.de		A3			
04	Hebel max500	30.06.2022	FEU			scale: 1:4		Status: Freigegeben	
03	Rohraufsatz	23.06.2022	TW						
02	Traglast	07.06.2022	FEU						
rev.	change	date	name						